

OUR PRICE:

\$ _____

FRAMESET

MAIN TUBESHi Tensile steel w/Cro-Moly seat tube
 STAYSHi Tensile steel
Frame weight 6.0 lb (2.75 gm)
 FORKHigh tensile steel
Axle-crown length, mm 397
 HEADSETSealed
Size 25.4/34.0/30.0
Stack height, mm 34.5

CONTROLS

HANDLEBARSteel, 60mm rise
Clamp diameter, mm 25.4
 STEMATB
 SHIFT LEVERSSRAM MRX
 BRAKE LEVERSAlloy, direct pull
 GRIPSOasis, dual density

DRIVETRAIN

FT DERAILLEURShimano TY-32
Cable routing Top pull
Attachment 31.8 mm/11/4"
 RR DERAILLEURShimano Altus GS
 CRANKSETSR XR128 48/38/28
Bolt hole circle, mm Riveted
 BBVP-BC55P semi-cartridge
Shell x axle, mm 68 x 122.5, Square
 CHAINKMC Z-51
Chain type 3/32"
Chain length (links) 110
 CASSETTEHG72 13-28, 7spd

WHEELSET

FRONT WHEELAlloy, QR hub, 36°, Aluminum alloy rim
E.R.D., mm 537
Rim strip Rubber
 FRONT TIREKnobby, center connect
Tire size 26 x 1.95
 REAR WHEELAlloy, QR hub, 36°, Aluminum alloy rim
E.R.D., mm 537
Rim strip Rubber
 REAR TIREKnobby, center connect
Tire size 26 x 1.95
 SPOKES14G stainless
Front, mm 265, 3x
Rear, mm 262/263, 3x
 INNER TUBESSchraeder valve

OTHER

SEATPOSTAlloy micro-adjust
Outer diameter, mm 29.2
 SADDLETrek Supersoft
 BRAKESAlloy direct pull
 PEDALSPlatform
Axle diameter 9/16"
 SEAT BINDERBolt, M6 x 50
 ADDITIONALS2 water bottle mounts (1 bottle on 13, 17W, 20W), rack mounts (no rack on 13")

Key features:

Rider: Casual double tracker or newbie

Frameset

Steel - strong, and durable

All-round geometry- Stable and forgiving

Wheelset

Alloy rims and quick release hubs- light, easy to operate

Center ridge tires- smooth and fast on pavement, wide for casual off-road riding

Components

Recreation level (Acera)- wide performance range, comfortable position, and powerful brakes

GEARING

	28	38	48
13	56	77	97
15	49	66	84
17	43	59	74
19	39	52	66
21	35	47	60
24	31	42	52
28	26	36	45

BIKE WEIGHT

31.7 lb.
14.39 kg.

COLORS

Trek Red/Bright Silver • Red/Black decals • Trek Red fork
 Warm Silver/Blackberry • Silver/Black decals • Warm Silver fork
 Candy Blue • Silver/White decals • Bright Silver fork

FIT

	Size	13	16.5	18	19.5	21	22.5	13W	17W	20W
Frame	Size	13	16.5	18	19.5	21	22.5	13W	17W	20W
Rider height	Inches	65	66	66	69	72	74	64	67	69
	Cm	164	167	168	175	184	188	162	169	174
Handlebar	Width, mm	580	580	600	600	600	600	580	580	600
Stem	Length, mm	105	105	105	120	135	135	105	120	120
	Angle	40	40	40	40	40	40	40	40	40
Crank	Length, mm	170	170	170	175	175	175	170	170	170
Seatpost	Length, mm	300	300	350	350	350	350	300	300	350
Steerer	Length, mm	128	128	128	143	183	223	128	143	183